

LAVENDER HARVESTER



Designed to make harvesting much easier and less labor intensive our harvester is a very efficient machine suitable for small to medium size growers. Its motorized power head cuts the crop at a preset height and blows the cuttings into a collection bag.

Single person operation.

Quick assembly time of approx. 2 minutes, slightly longer if sling removed.

Cuts and collects the crop in a single pass with negligible plant disturbance or ground compaction.

Adjustable fingers pick up the crop from the sides of the row and feed it over the cutter bar, ensuring all the crop is cut.

Adjustable cutter bar height, allowing plants / cuttings to be trimmed to the optimum height / length.

Circular cutter bar follows contours of shrubs, providing provides better cutting of sides and results in a finished shape pleasing to the eye.

Adjustable frame height to suit operator, with engine controls on side frame, the operator can walk directly behind the harvester or walk offset in a wheel track.

Frame is fully zinc plated for low maintenance.

Quick dismantling of harvester and compact storage - no spanners required! Main wheels have quick release lynch pins allow quick removal and folding of frame for compact storage or easy transporting in a vehicle.

Heavy-duty sling protects collection bag.

Quick release frame for the collection bag allows easy bag removal. Bag sits on a sling and is attached to the quick release frame with a bungy cord.

Extra harvesting bags available for different crops

Cutting height (at outside edge): adjustable from 100 to 550 mm

Note: Due to blade curve (1150 mm radius) the cutting height is 135mm higher in the centre of the harvester.

Cutting width: 1210 mm

Wheel track: 1610 mm front / 1435 mm rear

Wheel drive: none

Weight, dry: 46 kg

Collecting bin / bag: supplied bag

Dimensions: Ready to use: width = 1700 mm / length = tba mm including fingers

For Freighting (in crate): approx. 1.70 cu.m / approx. 120 kg

Engine: Husqvarna Zenoah G4K-D (used to be Komatsu Zenoah) 41.5cc air cooled 2-stroke gasoline engine

Fuel / oil mix 25:1

Eastern Farm Machinery Ltd. RR3, P.O. Box 3613, Guelph, Ontario, Canada, N1H 6P1

Tel 5197632400, Fax 5197633930, sales@easternfarmmachinery.com