



## **TX1200**

- Slopes
- Road Construction
- Reservoirs
- Swamps
- Naturalized Areas
- Wetlands

Technical specifications□
Model TX1200 □
Engine 45 hp Kubota, Turbo Diesel□
Fuel consumption 0.8-1.05 gal/hr□
Tank capacity 6.6 gal. □
Dead weight: 1606 lbs.□
Height 83", lift arms 7.8" □
Width 59"□
Height 38"□
Ground clearance of 6"□
Center of gravity above the earth 12.5"□
Drive Hydrostatic□
Speed ••- front / rear 6 mph□
Turning radius 0 °□
Slopes up to 55 °□
Minimum pressure 0.71 PSI□
For Linkage, Kat.1, max. 1100 lbs□
PTO drive - for Mechanical, 6 spline, 1000 RPM, □
Hydraulic ports - rear 1 double acting., 1 single acting. □
Hydraulic capacity 2.6gal., 3045 PSI□
Remote control range 2600 ft., 2.4 Ghertz□
Cutting table 63"-79", depending on the gear Forbehold for andringer i tekniske specifikationer m.m.

Eastern Farm Machinery Ltd. □
RR3,P.O. Box 3613□
Guelph,ON. Canada□
N1H 6P1□
Tel. 5197632400, Fax 5197633930□
sales@easternfarmmachinery.com