















SSQ LOADER

SSQ11		 Engine capacity 11,7 Hp  Hydraulic capacity 600 Kg  Hydraulic system 21,6 l/min	SSQ11 LOADER Engine: Honda GX390 - Displacement 389 cc Number of cylinders: 1 Start up: Electric Revolutions per minute: 3600 Cooling: air cooled Fuel: petrol Euro 95	Fuel tank capacity: 6,1 lt Drive system: Hydrostatic 4WD wheel motors Hydraulic tank capacity: 44 lt Standard tyres: 4.00x10 Tractor Steering: Skid steering Kerb weight: 575 Kg
SSQ13		 Engine capacity 12,8 Hp  Hydraulic capacity 600 Kg  Hydraulic system 21,6 l/min	SSQ13 LOADER Engine: Yamaha MX400 - Displacement 402 cc Number of cylinders: 1 Start up: Electric Revolutions per minute: 3600 Cooling: air cooled Fuel: petrol Euro 95	Fuel tank capacity: 6,1 lt Drive system: Hydrostatic 4WD wheel motors Hydraulic tank capacity: 44 lt Standard tyres: 5.00x10 Tractor Steering: Skid steering Kerb weight: 545 Kg
SSQ ECOQUAD*		 Engine capacity 2,2 Hp  Hydraulic capacity 600 Kg  Hydraulic system 18 lt/min	SSQ ECOQUAD LOADER Engine: ACM Revolutions per minute: 2200 Battery type: traction battery Voltage: 36V Battery capacity: 240Ah - 8,6Kw	Drive system: Hydrostatic 4WD wheel motors Hydraulic tank capacity: 27 lt Standard tyres: 4.00-10 Skid (Forklift tyres) Steering: Skid steering Kerb weight: 845 Kg
SSQ15D*		 Engine capacity 14,6 Hp  Hydraulic capacity 650 Kg  Hydraulic system 25,6 l/min	SSQ15D LOADER Engine: Kubota Z602 - Displacement 599 cc Number of cylinders: 2 Start up: Electric Revolutions per minute: 3200 Cooling: liquid cooled Fuel: diesel	Fuel tank capacity: 14 lt Drive system: Hydrostatic 4WD wheel motors Hydraulic tank capacity: 25 lt Standard tyres: 23x8.50-12 Tractor Steering: Skid steering Kerb weight: 654 Kg
SSQ22		 Engine capacity 22,1 Hp  Hydraulic capacity 650 Kg  Hydraulic system 28,8 l/min	SSQ 22 LOADER Engine: Honda HGX690 - Displacement 688 cc Number of cylinders: 2 Start up: Electric Revolutions per minute: 3600 Cooling: air cooled Fuel: petrol Euro 95	Fuel tank capacity: 9 lt Drive system: Hydrostatic 4WD wheel motors Hydraulic tank capacity: 44 lt Standard tyres: 22x11.00-8 All Trac Steering: Skid steering Kerb weight: 630 Kg

WORKY-QUAD
TRUE PERFORMANCE
IN A SMALL SIZE.



Data contained in this document is subject to change without notice and/or modification. Cast Group reserves the right to modify its products without obligation to communications. The images in this document are for the only a demonstrative purpose.

Data obtained with counterweights.
* Model available also with remote control.

