

GX 1500 makes the impossible possible. Never before has a tool carrier been able to adapt to any situation with perfection.

Gravity and ground clearance.

The center of gravity on the GX1500 can be moved to the extreme. Hydraulically adjusted between 10 and 55 cm, which provides optimal opportunities to drive on slopes up to 45 degrees, and on marsh land or water. This happens with a small touch on the remote control.

The machine has hydraulic suspension in all four corners for smooth running without vibration.



The powerful transmission sits in closed well tested gearboxes. We've only used the best components to ensure the highest possible efficiency. If the machine is equipped with a hydraulic shredder and not desired PTO operation, it also comes with a piston pump of 95 hp to the crusher.



Transmission / engine

The engine is the Caterpillar brand with 100 HP that provides great power to any tools one may want to put on the machine. There isn't any V-belts on the machine, this reduces the maintenance on this model GX 1500





Remote Control

We have developed the remote from scratch, and it is the only one on the market, that has two way communication, making it possible to get valuable information on how steep the slopes are, or how high the engine oil pressure and temperature is at all times.

The electronics are in fact so robust that the remote also is sold to industrial machinery. It uses 2.4 megahertz, which means that it has approved almost anywhere even at oil refineries. The remote has a guaranteed range exceeding 800 meters.





Coolers

The machine has a cooling capacity designed for operation in extreme heat. The radiator is fitted with a dust and pollen filter that effectively removes all foreign matter. As an option, GX1500 comes with reversible fan blades which are controlled from the remote.

3 point hitch, PTO.

The machine is fitted as standard with 3 point hitch on the rear end and front.

This allows the GX1500 to run all tools that a tractor can run. Our PTO is mechanical which means that 98% of the power is transmitted to the PTO and therefore no transmission loss here.

Туре:	GX 1500
Caterpillar E ngine	100 hp 4.4 L Turbo
Slopes up to	45 degrees in all directions
Weight	4840 lbs.
Speed forward /	(0-1.24) (0-3.1) (0-4.7) (0-
reverse	6.2)
Turning Radius	0 degrees
Width	63" to 91"
Height	43" to 67"
Length	122"
Centre of gravity	between 12" and 39"
above ground	



Application Areas: Roadside Embankments and Verges Reservoir and Lagoon Banks Bird and Nature Reserves Water Works and Treatment Plants Railway Embankments Ministry of Defence Sites Munitions and Bulk Fuel Installations All grass banks and revetments

River Walls and Watercourses Monuments and Heritage Sites Golf Courses Sewage Treatment Plants Airports and Airfields Firing Ranges

Eastern Farm Machinery Ltd. RR3, P.O. Box 3613 Guelph, Ontario, Canada, N1H 6P1 sales@easternfarmmachinery.com Tel. 5197632400, Fax 5197633930

Lynex reserves the right to change technical specifications, etc..