VC696

Hydraulic timber trailer

Trailer dimensions	Width 1360mm x height 1500mm x length 3800mm	
.oading area	Width 1250mm x height 750mm x length 2500mm x (ca 2.5m ³)	
Fotal weight	600kg	
oading capacity	1500kg	
Maximum reach of the crane	3.4m	
Maximum weight lifting at 3.4m	200kg	
Maximum weight lifting at 1.7m	350kg	
Rotator	GR10	
Rotation radius	+/- 90°	
Rotation radius of the rotator	infinite	
Grapple area	0.08m ²	
Maximum opening of grapple	750mm	and the second
Dil pressure	160bar	
Tyres	Low pressure tyres 22 / 11 – 8"	and the second second
Coupling	360 degrees rotatory coupling for 50mm hitch ball	

Speed 3 –5 km/h Waterproof electric remote control Hydraulic drive system helps the ATV move in hard conditions like deep snow, mud or stumps.

Hydraulic winch

4x4 hydraulic drive system

Rated line pull 800kg Speed 10 – 25m/min Remote control area 30m The winch helps to pull logs closer from inaccessible and dangerous areas. Std. on 350-II model

Std. on 350-II model



Radio controlled hydraulic winch placed on the crane construction.

Hydraulic unit

7.5HP 4-stoke petrol engine Oil tank 8 litres Dimensions 350mm x 350mm x 700mm Weight 30 kg

The hydraulic unit is fastened on the front rack of an ATV or on the back of an UTV or a pick-up truck. Provides the necessary oil flow and pressure to operate the crane and all the accessories.

Additional information:

Galvanized and powder-coated steel construction.

2 pairs of log bolster posts in standard kit (possible to add extra log bolster posts for smaller timber).

Log bolster posts can be moved on the main frame to adjust the load balance of the trailer.

Suitable for transporting timber up to 5 metres of length.

Most of the hydraulic distribution moves through the frame of the trailer, making for good protection against damage. Safe uploading of timber provided trough hydraulic support legs.

Complete, illustrated user / operator & CE safety instructions included.

Product	Code	Price
Hydraulic timber trailer	350-1/350-11	



Eastern Farm Machinery Ltd. 10 Nicholas Beaver Rd. Puslinch, ON., N0B 2J0 Tel. 5197632400, Fax 5197633930 sales@easternfarmmachinery.com

LOG BOLSTER POSTS KIT

el construction

Mounting additional posts allows transporting shorter logs.

Material	Galvanized and powder-coated stee
Dimensions	1300mm x 800mm
Weight	20kg
Nation	ALL DEGREENED

9	Product	Cod	
	Log bolster posts kit	21. M. 28-4	

TIPPING BOX

Galvanized and powder-coated steel construction. The tipping box can be easily mounted on the trailer by removing the logging post on the trailer and lifting the dumper onto the trailer. Dumper dumpy by 2 hydraulic cylinders.

Dimensions WxHxL Capacity Tipping angle Weight		1400mm x 400mm x 2100mm 1500kg 46° For 350-II only 200kg		nly
	Product		Code	Price
	Tipping box set	1.51 2		\$1950.00



EARTH BUCKET

Designed to lift and dig soft soil.

Capacity Weight Dimensions	60 litres 60kg 420mm x 420n	nm x 560mm	1. 1.
Product	1104204746	Code	Price
Earth bucket set	1123	Sertor A	\$465.00





Eastern Farm Machinery Ltd. 10 Nicholas Beaver Rd. Puslinch,ON., N0B 2J0 Tel. 5197632400, Fax 5197633930 sales@easternfarmmachinery.com