



# Model 2000 of the ST series

The ST-2000 sand spreader is easy-to-use and suitable for private land owners as well as service providers.



To adjust the quantity of bulk material, the rotational speed of the distribution shaft can be changed with a flow rate regulator. That way it is possible to spread a precise and optimal amount of material on the roads.



The transmission mechanism is protected by a strong housing that can be easily removed. Tensioning the chain and maintaining the equipment is easy and convenient.



An additional extension increases the volume of the spreader, making it possible to work longer with one loading.



Distribution shaft plates made of wear-resistant HARDOX steel guarantee the long working life of the sand spreader.



Durable rubber strips with a three-layer reinforcement guarantee a long working life and an even sanding outcome.

	ST-2000
Working width	2000 mm
Bucket volume (with extension)	800 (1250) l
Length of the working area (with extension) (200 g/m <sup>2</sup> )	3,4 (5,3) km
Tractor	40-100 hp
Weight (with extension)	277 (335) kg
Oil pressure	max 175 bar
Necessary oil flow	30-60 l/min
1/2" quick connection	2 pcs
Coupling	3-point (category 2)
Length x width x height	770 x 2150 x 920 mm

**Accessories:** extension, LED back lights and PVC cover.

Eastern Farm Machinery Ltd. □  
 10 Nicholas Beaver Rd. □  
 Puslinch, On. Canada, N0B 2J0 □  
 T. 5197632400 F 5197633930 □  
 sales@easternfarmmachinery.com