



Models 1000 and 1250 of the ST series


The smaller sand spreaders of the ST series are intended for sanding city streets using a small tractor.



The transmission mechanism is protected by a strong housing that can be easily removed. Tensioning the chain and maintaining the equipment is convenient.



A safety net prevents foreign bodies from entering the working area of the shafts.



A mixing shaft crushes bigger pieces of bulk material that have stuck together.



A check valve prevents the incorrect actuation of the sand spreader, thereby protecting the construction of the equipment.



By using an additional extension, it is possible to increase the volume of the spreader and sand a longer section of road with one loading.



Distribution shaft plates made of wear-resistant HARDOX steel guarantee the long working life of the sand spreader.



A durable reinforced rubber sheet is tensioned by plates made of special spring steel.



In addition to tilting, the sand spreader can also be emptied from beneath – between the distribution shaft and rubber by releasing spring plate levers on the sides. That way it is possible to remove bigger stones etc. that have entered the sand spreader through the safety net.

	ST-1000	ST-1250
Working width	1000 mm	1250 mm
Bucket volume (with extension)	190 (338) l	240 (426) l
Length of the working area (with extension) (200 g/m ²)	1,6 (2,9) km	1,6 (2,9) km
Tractor	- 45 hp	- 45 hp
Weight (with extension)	112 (135) kg	125 (157) kg
Oil pressure	max 175 bar	max 175 bar
Necessary oil flow	20-40 l/min	20-40 l/min
1/2" quick connection	2 pcs	2 pcs
Coupling	3-point (categories 1 and 0)	3-point (categories 1 and 0)
Length x width x height	815 x 1166 x 630 mm	815 x 1420 x 630 mm

Accessories: extension, LED back lights, PVC cover and flow rate regulator with hoses.

Eastern Farm Machinery Ltd. □
 10 Nicholas Beaver Rd. □
 Puslinch, On. Canada, N0B 2J0 □
 T. 5197632400 F 5197633930 □
 sales@easternfarmmachinery.com